

## PRODUCT SPECIFICATION SHEET

**PRODUCT NAME:** SAE/BCI GROUP 4D

**DESCRIPTION:** BATTERY, WET-MAINTENANCE Free, LEAD-ACID 12-VOLT SLI



**SEBANG**  
SEBANG GLOBAL BATTERY

**PHYSICAL CHARACTERISTICS:**

MODEL	LENGTH		WIDTH		HEIGHT		WEIGHT		ELECTROLYTE VOLUME	
	IN	MM	IN	MM	IN	MM	Lbs	Kg	Gal	ℓ
4D-6	20	508	8.74	221.996	9.49	241.046	83	37.682	2.62	9.9167
4D-7	20	508	8.74	221.996	9.49	241.046	82	37.228	2.62	9.9167

**PERFORMANCE CHARACTERISTICS (IN ACCORDANCE TO SAE J537 TEST STANDARDS):**

MODEL	CCA	CA	RC	AH	OTHER
	@ 0°F TO 7.2V	@ 32°F TO 7.2V	25A @ 77°F TO 10.50V	C/20 @ 77°F TO 10.50V	
4D-6	850(-30)	1020	270	138	N/A
4D-7	950(-30)	1140	300	150	N/A

**PRODUCT DESIGN FEATURES:**

- 1- SEALED, MAINTENANCE-FREE CONSTRUCTION WITH CALCIUM ALLOY GRIDS TO MAXIMIZE LIFE
- 2- INTERGRATED CHARGE STATUS "EYE" FOR QUICK AND CONVENIENT INSPECTIONS
- 3- DURABLE, IMPACT RESISTANCE POLYPROPYLENE CONTAINER AND COVER
- 4- PROPRIETARY SECONDARY COVER TO IMPROVE OUT-GASSING AND CONDENSATION RECOVERY
- 5- CONVENIENT "SUITECASE" STYLE HANDLE FOR EASY INSTALLATION AND HANDLING
- 6- RESIN SEALED AND FORGED TERMINAL BUSHINGS FOR CORROSION RESISTANCE
- 7- ANCHORED ELEMENTS FOR IMPROVED LIFE AND IMPROVED VIBRATION RESISTANCE
- 8- PROPRIETARY SEPARATOR MATERIALS TO RESIST OXIDATION AND IMPROVE LIFE IN HOTTER CLIMATES